

YXMXYC8020

行程: ±10mm

最大负荷: 8.5kgf

传动方式: 螺杆传动

最高速度: 20mm/sec

单向定位精度: 0.01mm

反复定位精度: ±0.001mm

反向间隙: 0.005mm

静态平行: 60um

运动平行: 10um

一般	公 差	STATE OF STA			備	註	合格成品,獨立包裝保存			機	型	N/A	
尺寸範圍	容許差	巡巡		館传动	表	處	1	衣各零件		料	碼	YXMXYC8020	
0.5 ~ 5 5 ~ 15	±0.05	The N	lark of Line	ar Motion	材	料	見零件表	き 數量	N/A/組	品	名	电动滑台MXC(8020双	双轴)
15 ~ 70	±0.08 ±0.1	審核日期			熱	處理				檔案	ミ 號	YXMXYC8020(客用])
$70 \sim 300$ $300 \sim 1000$	±0.2 ±0.3	繪圖	日其	2019/01/25	單	位	mm	圖紙規格	A3	4m.	= /.	版	т1
1000 ~ 1500	±0.5 ±0.5	設計	日其	2019/01/25	比	例	1:1.5	重量 2	2396.39	权	影	\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	11



